

Diesel Forklifts



CPCD120/140/150/160-C2Z-09

Item		Diesel Forklift-Pneumatic			
Identification		G Series			
Series		G Series			
Model		CPCD120-C2Z-09	CPCD140-C2Z-09	CPCD150-C2Z-09	CPCD160-C2Z-09
Rated capacity	lbs	26000	31000	33000	35000
Load center	in	36	36	36	36
Dimensions					
Overall height (overhead guard)	in	132	133	133	133
Overall length (with fork/without fork)	in	264	280	280	280
Overall width (single tire)	in	101	101	101	101
Min. turning radius (exterior) (a single tire is the same double tires)	in	175.2	187	187	187
Weight					
Total weight	lbs	39242	45195	46297	47399
Wheels, Chassis					
Tire size (front/rear)	in	11.00-20	12.00-20	12.00-20	12.00-20
Performance					
Max. traveling speed (loaded/unloaded)	mph	15.5/16.8	16.3/16.9	16.3/16.9	16.3/16.9
Engine mode		CUMMINS QSB6.7	CUMMINS QSB6.7	CUMMINS QSB6.7	CUMMINS QSB6.7
Engine rated power	HP/rpm	173/2200	200/2200	200/2200	200/2200
Engine rated torque	(ft*lb)/rpm	650/1300	730/1300	730/1300	730/1300
Emission standard		T4F/StageV	T4F/StageV	T4F/StageV	T4F/StageV
Piston displacement	L	6.7	6.7	6.7	6.7
Drive axle mode		Meritor	Kessler	Kessler	Kessler