

Diesel Forklifts



CPCD15/18



CPCD20/25/30/35

Item	Diesel Forklift-Pneumatic (3000-7000 lbs. Capacity)						
Identification	H3 Series						
Series	H3 Series						
Model	CPCD15	CPCD18	CPCD20	CPCD25	CPCD30	CPCD35	
Rated capacity	lbs	3000	3500	4000	5000	6000	7000
Load center	in	24	24	24	24	24	24
Dimensions							
Overall height (overhead guard)	in	84	84	84.7	84.7	85.5	85.5
Overall length (with fork/without fork)	in	126.0/89.8	126.7/90.5	137.8/101.7	146/103.9	150.3/108.3	151/109
Overall width (single tire)	in	42.1	42.1	45.3	45.3	48.3	48.3
Min. turning radius (exterior) (a single tire is the same double tires)	in	75.2	76.0	85.5	88.3	94.6	95.3
Weight							
Total weight	lbs	6079	6365	7540	8377	9634	10582
Wheels, Chassis							
Tire size (front/rear)	in	6.50-10-10PR/ 5.00-8-8PR	6.50-10-10PR/ 5.00-8-8PR	7.00-12-12PR/ 6.00-9-10PR	7.00-12-12PR/ 6.00-9-10PR	28×9-15-12PR/ 6.50-10-10PR	28×9-15-14PR/ 6.50-10-10PR
Performance							
Max. traveling speed (loaded/unloaded)	mph	10.6/11.2	10.6/11.2	10.6/11.8	10.6/11.8	11.2/11.8	11.8/11.8
Engine mode		Kubota V2403		Kubota V2403-CR-TE5B			
Engine rated power	HP/rpm	45.1/2400		57.9/2400			
Engine rated torque	(lb.ft)/rpm	116/1600		146.4/1600			
Emission standard		T4F		T4F			
Engine cylinder number		4		4			
Piston displacement	L	2.434		2.434			