

## LPG Forklifts-Pneumatic Tire



CPYD15/18



CPYD20/25/30/35

Item	LPG Forklift-Pneumatic (3000-3500 lbs. Capacity)			LPG Forklift-Pneumatic (4000-7000 lbs. Capacity)			
	H3 Series			H3 Series			
Model		CPYD15	CPYD18	CPYD20	CPYD25	CPYD30	CPYD35
Rated capacity	lbs	3000	3500	4000	5000	6000	7000
Load center	in	24	24	24	24	24	24
<b>Dimensions</b>							
Overall height (overhead guard)	in	84	84	84.7	84.7	85.5	85.5
Overall length (with fork/without fork)	in	126.0/89.8	126.7/90.5	137.8/101.7	146/103.9	150.3/108.3	151/109
Overall width (single tire)	in	42.1	42.1	45.3	45.3	48.3	48.3
Min. turning radius (exterior) (A single tire is the same double tires)	in	75.2	76.0	85.5	88.3	94.6	95.3
<b>Weight</b>							
Total weight	lbs	6079	6365	7540	8377	9634	10582
<b>Wheels, Chassis</b>							
Tire size (front/rear)	in	6.50-10-10PR /5.00-8-8PR	6.50-10-10PR /5.00-8-8PR	7.00-12-12PR/ 6.00-9-10PR	7.00-12-12PR/ 6.00-9-10PR	28×9-15-12PR/ 6.50-10-10PR	28×9-15-14PR/ 6.50-10-10PR
<b>Performance</b>							
Max. traveling speed (loaded/unloaded)	mph	10.6/11.2	10.6/11.2	10.6/11.2	10.6/11.2	11.2/11.8	11.2/11.8
Engine mode		KUBOTA WG2503		KUBOTA WG2503/Mitsubishi 4G64(PSI)			
Engine rated power	HP/rpm	GAS:57.4/2600 LPG:58.3/2600		GAS:57.4/2600 LPG:58.3/2600/GAS:64.3/2700 LPG:61.6/2700			
Engine rated torque	(lb.ft)/rpm	GAS:120.4/1800 LPG:128.1/1400		GAS:128.7/1400 LPG:120.7/1800/GAS:125.4/2400 LPG:123.9/1600			
Engine cylinder number		4		4			
Piston displacement	L	2.491		2.491/2.351			

Option: Dual fuel