

Diesel Forklifts



CPCD40/45/50



CPCD55/60/70/85/100

Item	Diesel Forklift-Pneumatic (8000-10000 lbs. Capacity)				Diesel Forklift-Pneumatic (11000-22000 lbs. Capacity)				
	G3 Series				G Series				
Series	G3 Series				G Series				
Model	CPCD40	CPCD45	CPCD50	CPCD55	CPCD60	CPCD70	CPCD85	CPCD100	
Rated capacity	lbs	8000	9000	10000	11000	13000	15500	18500	22000
Load center	in	24	24	24	24	24	24	24	24
Dimensions									
Overall height (overhead guard)	in	91.3	91.3	91.3	96.5	96.5	96.5	100.8	100.8
Overall length (with fork/without fork)	in	171/123	173/125	175/127	185.4/137.4	188.6/140.6	190.6/142.6	204/156	213.8/165.8
Overall width (single tire)	in	60.6	60.6	60.6	80.5	80.5	80.5	85.2	85.2
Min. turning radius (exterior) (a single tire is the same double tires)	in	111.6	113.4	115.7	127.6	129.9	132.7	143.7	153.5
Weight									
Total weight	lbs	14352	15080	16424	18300	19950	21300	25500	27900
Wheels, Chassis									
Tire size (front/rear)	in	300-15-18PR/7.00-12-14PR			8.25-15-14PR/ 8.25-15-14PR	8.25-15-14PR/ 8.25-15-14PR	8.25-15-14PR/ 8.25-15-14PR	9.00-20-14PR/ 9.00-20-14PR	9.00-20-14PR/ 9.00-20-14PR
Performance									
Max. traveling speed (loaded/unloaded)	mph	14.3/15.5			17.4/19.6	17.1/19.5	16.9/19.4	17.0/19.5	16.3/19.3
Engine mode		Cummins QSF3.8			Cummins QSF3.8T4F				
Engine rated power	HP/rpm	74/2200			119.3/2200				
Engine rated torque	(lb.ft)/rpm	295/1300			360/1600				
Emission standard		T4F			T4F				
Engine cylinder number		4			4				
Piston displacement	L	3.8			3.8				