

Warehouse Truck-Order Picker



OPSM



OPS15



OPDS15

Model		OPSM	OPS15	OPDS15			
Type		Order picker	Order picker	Order picker	Order picker	Order picker	Order picker
Mast type		-	3-stage mast	256in	315in	362in	413in
Loading capacity	lbs	330	3000	3000	3000	3000	3000
Load center	in	-	24	24	24	24	24
Driving mode		Stand-on	Walkie	Stand-up rider	Stand-up rider	Stand-up rider	Stand-up rider
Wheels type		PU	Polyurethane	PU	PU	PU	PU
lift height	in	118(lifting height of partform)	197/276/354	187	246	294	345
Max.extend height	in	≈197	284.6/363.4/442.1	292.4±0.8	351.5±0.8	398.7±0.8	449.9±0.8
Mast lowered height	in	19.7	94.9/121.3/147.6	147.5±0.8	177.1±0.8	200.7±0.8	226.3±0.8
Overall length	in	60	126	149.8±0.8	149.8±0.8	149.8±0.8	149.8±0.8
Overall width	in	30	43.3/53.2	47.6/61.2	47.6/61.2	47.6/61.2	47.6/61.2
Min.Turning radius	in	51	70.9	87.4±0.8	87.4±0.8	87.4±0.8	87.4±0.8
Min.Aisle width for pallets 800×1000	in	68.9	55.1	66.1	66.1	66.1	66.1
Travel speed,laden/unladen	mph	2.8	4.8/5.0	6.2/6.2	6.2/6.2	6.2/6.2	6.2/6.2
Lift speed,laden/unladen	in/s	5.5	0-5.9/0-9.8	11.0/11.8	11.0/11.8	11.0/11.8	11.0/11.8
Battery voltage/capacity	V/Ah	24V/105(250)Ah	24/700(1100)	80/560	80/560	80/560	80/560
Controller		CURTIS	CURTIS	CURTIS	CURTIS	CURTIS	CURTIS
Battery weight	lbs	52×2(70×4)	1220(1700)	2960(2900-3020)	2960(2900-3020)	2960(2900-3020)	2960(2900-3020)
Service weight with battery	lbs	1500/1540	7740	15410	16210	16810	17610