

Walk-Behind Stacker



CBS10J-K



CDD12J-K



CTD16-960H

Model	CBS10J-K		CDD12J-K		CTD16-960H
Type	Semi-electric (Straddle)		Straddle		Straddle
Mast type	Single mast	2-Stage STD	Single mast	2-Stage STD	Full free 3-stage
Loading capacity	2000 (Rated traction weight)		2400 (Rated traction weight)		3500
Load center	24		24		24
Operating type	Handle		Pedestrian propelled		Walkie
Wheels type	Nylon/polyurethane		Polyurethane		PU
Lift height	63	79/98/118/138	63	79/98/118/138	177.2/185.0/196.9/212.6
Max. extend height	84	103/123/142/162	83	100/120/140/160	196.7/204.7/216.5/236.2
Mast lowered height	84	65/75/84/94	83	62/72/82/92	81.2/83.9/87.8/93.0
Overall length	73		70		75.2
Overall width	43-59		45-61		31.5
Min. turning radius	59		53		59
Min. aisle width for pallets 1000×1200	92.7-96.5		87		79.9
Travel speed	-		2.48/2.61		3.1/3.4
Lift speed	3.07/5.71	3.00/5.63	3.6/5.4		25.6/35.4
Battery voltage/capacity	12/120		2×12/100		24/270
Controller	-		CURTIS		ZAPI
Battery weight	72		2×54		539
Service weight with battery	870	970/988/1000/1050	1190	1272/1296/1320/1344	3320